

Inspire White 4140lm 3000K Ra>80 DALI-2 / Push Dim

Article code: 212081  
EAN: 7021982120817



Electrical

System wattage: 34W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 8, B16: 13, C10: 12, C16: 20  
Leakage current (mA): 0.29

Light technic

Type of light source: LED  
Luminous flux: 4140lm  
Efficacy: 122 lm/W  
Colour temperature: 3000K  
Colour rendering (CRI): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L80/B20>100,000  
Lifetime: L90>50,000  
Light distribution: Direct/Indirect 50/50%  
Optic: Cubic Optic Black  
UGR: UGR<10  
Photobiological safety: RG 1

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class I  
IP Class: IP20

Energy and approvals

Contains light source of energy class: D  
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium  
Colour: White  
Optics: Polycarbonat (PC)

Mounting/Connection

Mounting: Suspended, Indoor  
Wire set: 2x2m wire kit  
Cable: Cable 5x0,75mm<sup>2</sup> 2,5m

Dimensions

Length (mm) L: 1241  
Width (mm) W: 38  
Height (mm) H: 67  
Weight (kg) gross/net: 3.1 / 2.7

Packaging

Packing dimensions (mm): 1365 x 90 x 61

