

# Langfoss Mini



## Langfoss Mini Graphite 4850lm 3000K Ra>70 On/Off

Article code: 641938  
 EAN: 7021986419382  
 Replaces: 641912



### Electrical

System wattage: 35W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 8, B16: 12, C10: 12, C16: 20

### Light technic

Type of light source: LED  
 Light source included: Yes  
 Luminous flux: 4850lm  
 Efficacy: 139 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>70  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B50>100,000  
 Lifetime: L94>50,000  
 Minimum ambient temperature: -40°C  
 Light distribution: Asymmetric  
 Optic: Lens

### Control/Dimming

Type: On/Off

### Protection

Luminaire class: Class I  
 IK Class: IK07  
 IP Class: IP66  
 Integrated surge protection: Integrated (min. 4 kV)

### Materials and finish

Housing: Die-cast aluminium  
 Colour: Graphite  
 Optics: Tempered glass

### Mounting/Connection

Mounting: Indoor / Outdoor  
 Cable: Cable 3x1mm<sup>2</sup> 2m, H07RN-F  
 Wind projected area: 0,0756m<sup>2</sup> - Max 10,2 kg

### Dimensions

Length (mm) L: 362  
 Width (mm) W: 265  
 Height (mm) H: 85  
 Weight (kg) gross/net: 6.55 / 5.7

### Packaging

Packing dimensions (mm): 395 x 280 x 100

