


LEDDim Smart




Smart dimmer for mounting to wall box (EU) Bluetooth communication (BLE) and control via App. Setting of minimum level, input for button with dimming function. Five-year system warranty for dimmer when it is used together with SG products.

LEDDim Smart



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
LEDDim Smart				
 820412 LEDDim Smart White 400VA	IP20	Trailing edge dimming	Recessed, Indoor	L84 x W84 x H48
 820413 LEDDim Smart 2-pole White 400VA	IP20	Trailing edge dimming	Recessed, Indoor	L84 x W84 x H48
Accessories				
 820352 LEDDim 350/400/Smart White ABB Adapter Polycarbonat (PC)				L55 x W55 x H10
 820353 LEDDim 350/400/Smart White Schneider Adapter Polycarbonat (PC)				L56 x W56 x H12
 820417 LEDDim 350/400/Smart Black SG Front Polycarbonat (PC)				L83 x W83 x H29
 820418 LEDDim 350/400/Smart Silver Elko Adapter ABS				L55 x W55 x H12
 820424 LEDDim 350/400/Smart White SG Front Polycarbonat (PC)				L83 x W83 x H23
 820483 LEDDim Smart Color Controller White SG Smart/ Remote Control RF * / Push Dim				L175 x W45 x H27