

# Light sources E27









E27 LED dimmable light source with five-year system warranty if used together with a SG luminaire.

# Light sources E27






## Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
<b>10W</b>				
 830911 <b>E27 806lm 2700K Ra&gt;90</b> <b>10W</b> 81 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø60 x L110
 830913 <b>E27 LED DimToWarm 806lm</b> <b>2000-2800K Ra&gt;80</b> <b>10W</b> 81 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø60 x L110
 830914 <b>E27 820lm 3000K Ra&gt;90</b> <b>10W</b> 82 lm/W SDCM:4 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø60 x L121
<b>15W</b>				
 830916 <b>E27 LED White 1200lm 2700K Ra&gt;90</b> <b>15W</b> 80 lm/W SDCM:3 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø95 x L136
 830917 <b>E27 LED White DimToWarm 1200lm</b> <b>2000-2800K Ra&gt;80</b> <b>15W</b> 80 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø95 x L135
 830918 <b>E27 LED White 1200lm 3000K Ra&gt;90</b> <b>15W</b> 80 lm/W SDCM:3 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø95 x L136
<b>4W</b>				

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 830912 <b>E27 E27 Filament 545lm 2700K</b> <b>Ra&gt;80</b> <b>4W LED</b> 136 lm/W SDCM:6 L70/B50>15,000 Direct,		Trailing edge dimming		Ø70 x L125
<b>5W</b>				
 830922 <b>E27 LED White DimToWarm 350lm</b> <b>2000-2800K Ra&gt;80</b> <b>5W</b> 70 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø45 x L79
<b>6W</b>				
 831003 <b>E27 LED E27 450lm 2700K Ra&gt;90</b> <b>6W</b> 75 lm/W SDCM:3 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø60 x L110