

Rax 200 U19



Recessed LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>50,000, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and simple mounting. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector.

Rax 200 U19








Product- and environment images




Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
14W				
 <p>8246087740 • Rax 200 U19 White 1580lm 3000K Ra>80 DALI-2 14W LED 113 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor	Ø223 x H167
 <p>8246087766 • Rax 200 U19 White 1630lm 4000K Ra>80 DALI-2 14W LED 116 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor	Ø223 x H167
19W				
 <p>8246087805 • Rax 200 U19 White 2360lm 4000K Ra>80 DALI-2 19W LED 124 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor	Ø223 x H167
27W				
 <p>8246087821 • Rax 200 U19 White 3100lm 3000K Ra>80 DALI-2 27W LED 115 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø223 x L230 x H167
 <p>8246087834 • Rax 200 U19 White 3210lm 4000K Ra>80 Trailing edge dimming 27W LED 119 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	Trailing edge dimming	Recessed, Indoor	Ø223 x L230 x W223 x H167

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246087847 • Rax 200 U19 White 3210lm 4000K Ra>80 DALI-2 27W LED 119 lm/W SDCM:2 L90/B10>100,000 Beam: 66°, Direct, Satin Matt Reflector</p>	Class II IP20	DALI-2	Recessed, Indoor 5 pol Linect / screwless terminal block	Ø223 x L230 x H167

• = This article is produced by order, with an expected delivery time of 3-4 weeks.