

SENSE IP65



SENSE IP65 599x599 White 5160lm 4000K Ra>90 DALI-2 / Push Dim

Article code: 8246096278
EAN: 5703821181433



• = This article is produced by order, with an expected delivery time of 3-4 weeks.



Electrical

System wattage: 43W
Voltage: 220-240V
Frequency (Hz): 50/60Hz
Max. luminaires per circuit breaker: B10: 12, B16: 20, C10: 21, C16: 34
Leakage current (mA): 0.29

Light technic

Type of light source: LED
Luminous flux: 5160lm
Efficacy: 120 lm/W
Colour temperature: 4000K
Colour rendering (CRI): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L80/B50>100,000
Lifetime: L90/B10>50,000
Light distribution: Direct
Optic: Prism Optic
UGR: UGR<19
Visible flicker (PstLM): 0,07
Stroboscopic flicker (SVM): 0,01

Control/Dimming

Type: DALI-2 / Push Dim

Protection

Luminaire class: Class I
IK Class: IK07
IP Class: IP54/IP65

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Sheet steel
Colour: White smooth (Ral 9016 gloss 30)
Optics: Tempered glass

Mounting/Connection

Mounting: Recessed, Indoor
Module: 599x599 C, Clip-in Ceiling
Cable: Cable 5x0,75mm² 2,5m Halogen free

Dimensions

Length (mm) L: 599
Width (mm) W: 599
Height (mm) H: 93
Weight (kg) gross/net: 12.7 / 12.1

Packaging

Packing dimensions (mm): 625 x 605 x 97

