

# Sense Opalprism 300x1200



## 300x1200 Plaque de plâtre/Troldtekt Support

Codes-articles: 8249045019  
 EAN: 5703821178969  
 Remplace: 8249044502



Intérieur  
 300x1200



### Montage/Connexion

Montage:  
 Module:

### Dimensions

Longueur (mm) L: 1240  
 Largeur (mm) W: 340  
 Hauteur (mm) H: 40  
 Poids (kg) brutto/netto: 1.5 / 1.3

### Emballage

Dimensions de l'emballage (mm): 1250 x 370 x 50

Sense Panels & Driver Kits									
	CU	CU/CA	BA	SENSE 3000lm 5000lm 5000lm PHASE DIM (700mA)	SENSE 4000lm 5000lm 5000lm NON DIM (1000mA)	SENSE 5000lm 5000lm 5000lm NON DIM (1400mA)	SENSE 3000lm 5000lm 5000lm DALI (800mA)	SENSE 4000lm 5000lm 5000lm DALI (1000mA)	SENSE 5000lm 5000lm 5000lm DALI (1400mA)
SENSE OPAL 3-4000lm LED 3000K	80	3	110	2750lm UGR<22 21W/129lm/W	4000lm UGR<22 31.2W/127lm/W	*	2750lm UGR<22 21W/129lm/W	4000lm UGR<22 31.2W/127lm/W	*
SENSE OPAL 3-4000lm LED 4000K	80	3	110	2650lm UGR<22 21W/124lm/W	4000lm UGR<22 31.5W/130lm/W	*	2750lm UGR<22 21W/126lm/W	4000lm UGR<22 31.5W/130lm/W	*
SENSE OPAL 5000lm LED 3000K	80	3	110	2650lm UGR<22 21W/124lm/W	3900lm UGR<22 31.5W/127lm/W	5000lm UGR<22 42W/121lm/W	2850lm UGR<22 21W/126lm/W	3900lm UGR<22 31.5W/127lm/W	5000lm UGR<22 42W/118lm/W
SENSE OPAL 5000lm LED 4000K	80	3	110	2750lm UGR<22 21W/131lm/W	4000lm UGR<22 31.5W/127lm/W	5000lm UGR<22 42W/121lm/W	2750lm UGR<22 21W/131lm/W	4000lm UGR<22 31.5W/127lm/W	5000lm UGR<22 42W/121lm/W
SENSE PRISM 3-4000lm LED 3000K	80	3	90	2650lm UGR<17 21W/126lm/W	3750lm UGR<19 31.5W/124lm/W	*	2650lm UGR<17 21W/126lm/W	3750lm UGR<19 31.5W/124lm/W	*
SENSE PRISM 3-4000lm LED 4000K	80	3	90	2750lm UGR<17 21W/131lm/W	4000lm UGR<19 31.5W/129lm/W	*	2750lm UGR<17 21W/131lm/W	4000lm UGR<19 31.5W/129lm/W	*
SENSE PRISM 5000lm LED 3000K	80	3	90	2650lm UGR<17 21W/126lm/W	3750lm UGR<17 31.5W/118lm/W	4000lm UGR<19 42W/110lm/W	2650lm UGR<17 21W/126lm/W	3750lm UGR<17 31.5W/118lm/W	4000lm UGR<19 42W/110lm/W
SENSE PRISM 5000lm LED 4000K	80	3	90	2750lm UGR<17 21W/131lm/W	3750lm UGR<17 31.5W/118lm/W	4000lm UGR<19 42W/110lm/W	2750lm UGR<17 21W/131lm/W	3750lm UGR<17 31.5W/118lm/W	4000lm UGR<19 42W/110lm/W

Efficiency calculations are incl. driver  
 incl. driver: 7.14% loss depending on driver

