

# Arco Air



Decorative LED lamp for wall and garden. Made of powder-coated corrosion-proof aluminium. Installed with dimmable, replaceable GU10 LED bulb (included) that illuminates a top reflector, thus giving soft light with a pleasant effect. Impact-resistant with IK08 and phenolic screw to prohibit access to the light source.

# Arco Air








## Product- and environment images




# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
<b>2700K</b>				
 <p>623620  <b>Arco Air Graphite 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge dimming</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<p><b>Class I</b>  <b>IP54</b>  <b>IK08</b></p>	<p>Trailing edge            dimming</p>	<p>Pole, wall, bollard or earthing rod,            Outdoor            Screwless terminal block</p>	<p>Ø160 x H963</p>
 <p>623621  <b>Arco Air Graphite R 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge dimming</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<p><b>Class I</b>  <b>IP54</b>  <b>IK08</b></p>	<p>Trailing edge            dimming</p>	<p>Pole, wall, bollard or earthing rod,            Outdoor            Screwless terminal block</p>	<p>Ø160 x H400</p>
 <p>623622  <b>Arco Air Wall Graphite 75lm 2700K</b>  <b>Ra&gt;90 Trailing edge dimming</b>  <b>6W LED</b>            13 lm/W SDCM:2            L70/B50&gt;50,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<p><b>Class I</b>  <b>IP54</b>  <b>IK08</b></p>	<p>Trailing edge            dimming</p>	<p>Surface, Outdoor            Screwless terminal block</p>	<p>W160 x H356 x D219</p>
<b>3000K</b>				
 <p>623623  <b>Arco Air Graphite 100lm 3000K</b>  <b>Ra&gt;80 Trailing edge dimming</b>  <b>6.2W LED</b>            16 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<p><b>Class I</b>  <b>IP54</b>  <b>IK08</b></p>	<p>Trailing edge            dimming</p>	<p>Pole, wall, bollard or earthing rod,            Outdoor            Screwless terminal block</p>	<p>Ø160 x H963</p>
 <p>623624  <b>Arco Air Graphite 100lm 3000K</b>  <b>Ra&gt;80 Trailing edge dimming</b>  <b>6.2W LED</b>            16 lm/W SDCM:4            L70/B50&gt;25,000            Beam: 360°, Direct/Indirect, Glass            Clear</p>	<p><b>Class I</b>  <b>IP54</b>  <b>IK08</b></p>	<p>Trailing edge            dimming</p>	<p>Pole, wall, bollard or earthing rod,            Outdoor            Screwless terminal block</p>	<p>Ø160 x H400</p>

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 623625 <b>Arco Air Wall Graphite 100lm</b> 3000K Ra>80 Trailing edge dimming 6.2W LED 16 lm/W SDCM:4 L70/B50>25,000 Beam: 360°, Direct/Indirect, Glass Clear	<b>Class I</b> <b>IP54</b> <b>IK08</b>	Trailing edge dimming	Outdoor Screwless terminal block	W160 x H356 x D219

## Accessories

 600581 <b>Arco Air Anchoring set Steel</b>				Ø148 x H245
--	--	--	--	-------------