

# Circulus Pendant



## Circulus Pendant Black 1530lm 3000K Ra>80 Trailing edge dimming

Article code: 214006  
EAN: 7021982140068



### Electrical

Wattage: 15W  
System wattage: 15W  
Voltage: 220-240V  
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

### Light technic

Type of light source: LED  
Luminous flux: 1530lm  
Efficacy: 102 lm/W  
Colour temperature: 3000K  
Colour rendering (CRI): Ra>80  
MacAdams factor: SDCM: 3  
Lifetime: L80/B10>50,000  
Lifetime: L70/B50>100,000  
Light distribution: Direct  
Optic: Opal  
Beam angle: 110°  
UGR: UGR<25  
Photobiological safety: RG 0

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class I  
IP Class: IP20

### Energy and approvals

Contains light source of energy class: B  
Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Steel  
Colour: Black (RAL 9004)  
Optics: Acrylic (PMMA)

### Mounting/Connection

Mounting: Suspended, Indoor  
Connection: Screwless terminal block

### Dimensions

Height (mm) H: 280  
Diameter (mm) D: 360  
Weight (kg) gross/net: 3 / 2.3

### Packaging

Packing dimensions (mm): 370 x 370 x 95

