



Etne is the perfect choice for storage rooms, hobby rooms and corridors, providing good light and wide light distribution. Easy installation directly in the ceiling or on the ceiling box, with loopable screwless terminal blocks and prepared for hidden or open cabling. Etne with a PIR sensor turns the light on at movement and switches off after a chosen time, thereby saving energy. The sensor does not detect through walls or doors. The PIR sensor also features an adjustable daylight sensor that only turns on the light when it's dark. Etne with a PIR sensor can act as a master controlling up to ten other luminaires (slaves).

Etne







Product- and environment images



Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
3000K				
 <p>143090 Etne White 730lm 3000K Ra>80 On/Off 11W LED 66 lm/W SDCM:3 L80/B10>50,000 Beam: 114°, Direct, Opal</p>	<p>Class II IP20 IK07</p>	<p>On/Off</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>Ø220 x H50</p>
 <p>143091 Etne White 790lm 3000K Ra>80 PIR Sensor 10W LED 79 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 114°, Direct, Opal</p>	<p>Class II IP20 IK07</p>	<p>PIR Sensor</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>Ø220 x H59</p>
4000K				
 <p>143094 Etne White 820lm 4000K Ra>80 On/Off 10W LED 82 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 114°, Direct, Opal</p>	<p>Class II IP20 IK07</p>	<p>On/Off</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>Ø220 x H50</p>
 <p>143095 Etne White 820lm 4000K Ra>80 PIR Sensor 10W LED 82 lm/W SDCM:3 L90/B10>50,000, L80/B10>100,000 Beam: 114°, Direct, Opal</p>	<p>Class II IP20 IK07</p>	<p>PIR Sensor</p>	<p>Surface, Indoor Screwless terminal block</p>	<p>Ø220 x H59</p>