

Frame Round



Frame Round Black 670lm 4000K Ra>80 Trailing edge dimming

Article code: 605081
EAN: 7021986050813



• = This article is produced by order, with an expected delivery time of 3-4 weeks.




Electrical

System wattage: 7W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 670lm
Efficacy: 96 lm/W
Colour temperature: 4000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B20>100,000
Lifetime: L80/B20>75,000
Light distribution: Direct
Optic: Opal
Beam angle: 110°
Photobiological safety: RG 0



Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP66
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: UV-stabilized polycarbonate

Mounting/Connection


Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Height (mm) H: 77
Diameter (mm) D: 270
Weight (kg) gross/net: 2.39 / 1.9

Packaging

Packing dimensions (mm): 278 x 275 x 92



7 0 2 1 9 8 6 0 5 0 8 1 3