

Frame Square








Design: Holscher Design. Frame has a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Frame is available in round, square and rectangular shapes in different sizes. Made of die-cast, powder-coated aluminium in black, white or graphite. Flat diffuser made of UV-stabilised opal polycarbonate. Versions with sensors and twilight are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. IP66 and IK10.





Frame Square



Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
Black, 3000K				
 <p>605251 Frame Square Black 630lm 3000K Ra>80 Trailing edge dimming 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor / Outdoor Screwless terminal block</p>	<p>L240 x W240 x H77</p>
 <p>605252 Frame Square Black 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Twilight</p>	<p>Surface, Indoor / Outdoor Screwless terminal block</p>	<p>L240 x W240 x H77</p>
Black, 4000K				
 <p>605281 ● Frame Square Black 660lm 4000K Ra>80 Trailing edge dimming 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor / Outdoor Screwless terminal block</p>	<p>L240 x W240 x H77</p>
Graphite, 3000K				
 <p>605261 Frame Square Graphite 630lm 3000K Ra>80 Trailing edge dimming 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor / Outdoor Screwless terminal block</p>	<p>L240 x W240 x H77</p>
 <p>605262 Frame Square Graphite 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	<p>Class II IP66 IK10</p>	<p>Twilight</p>	<p>Surface, Indoor / Outdoor Screwless terminal block</p>	<p>L240 x W240 x H77</p>
Graphite, 4000K				

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>605291 Frame Square Graphite 660lm 4000K Ra>80 Trailing edge dimming 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	Class II IP66 IK10	Trailing edge dimming	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
White, 3000K				
 <p>605241 Frame Square White 630lm 3000K Ra>80 Trailing edge dimming 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	Class II IP66 IK10	Trailing edge dimming	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
 <p>605242 Frame Square White 630lm 3000K Ra>80 Twilight 7W LED 90 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	Class II IP66 IK10	Twilight	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77
White, 4000K				
 <p>605271 Frame Square White 660lm 4000K Ra>80 Trailing edge dimming 7W LED 94 lm/W SDCM:3 L70/B20>100,000, L80/B20>75.000 Beam: 110°, Direct, Opal</p>	Class II IP66 IK10	Trailing edge dimming	Surface, Indoor / Outdoor Screwless terminal block	L240 x W240 x H77

• = This article is produced by order, with an expected delivery time of 3-4 weeks.