

Frame



Frame Graphite 670lm 3000K Ra>80 Trailing edge dimming

Article code: 605561
EAN: 7021986055610




Electrical

System wattage: 8W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

Light technic

Type of light source: LED
Luminous flux: 670lm
Efficacy: 84 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>80
MacAdams factor: SDCM: 3
Lifetime: L70/B20>100,000
Lifetime: L80/B20>75,000
Light distribution: Direct
Optic: Opal
Beam angle: 110°
Photobiological safety: RG 0



Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II
IK Class: IK10
IP Class: IP66
Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: C
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium
Colour: Graphite
Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
Connection: Screwless terminal block

Dimensions

Length (mm) L: 320
Width (mm) W: 180
Height (mm) H: 77
Weight (kg) gross/net: 2.47 / 1.9

Packaging

Packing dimensions (mm): 328 x 188 x 92

