

## Inspire 1200 Black prism 3510lm 3000K Ra>80 DALI-2

Article code: 212493  
 EAN: 7021982124938




### Electrical

System wattage: 29W  
 Voltage: 220-240V  
 Frequency (Hz): 50/60Hz  
 Max. luminaires per circuit breaker: B10: 12, B16: 20, C10: 21, C16: 29  
 Leakage current (mA): 0.29

### Light technic

Type of light source: LED  
 Luminous flux: 3510lm  
 Efficacy: 121 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L90/B10>100,000  
 Lifetime: L96>50,000  
 Light distribution: Direct/Indirect  
 Optic: Prism Optic  
 UGR: UGR<19  
 Visible flicker (PstLM): <1  
 Stroboscopic flicker (SVM): <0,4  
 Photobiological safety: RG 0



### Control/Dimming

Type: DALI-2  
 Driver: 800mA

### Protection

Luminaire class: Class I  
 IP Class: IP20

### Energy and approvals

Contains light source of energy class: B  
 Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
 Optics: Polycarbonat (PC)

### Mounting/Connection

Mounting: Suspended, Indoor  
 Module: 1200  
 Wire set: 2x2m wire kit  
 Cable: Cable 5x0,75mm<sup>2</sup> 2,5m

### Dimensions

Length (mm) L: 1240  
 Width (mm) W: 38  
 Height (mm) H: 67  
 Weight (kg) gross/net: 3.6 / 3.3

### Packaging

Packing dimensions (mm): 1365 x 90 x 61

