Jupiter Pro Soft

Jupiter Pro Soft White 1850lm 4000K Ra>90 Trailing edge dimming

Article code: EAN:

940356 7021989403562

• = This article is produced by order, with an expected delivery time of 3-4 weeks.

Electrical		
System wattage:	22W	
Voltage:	220-240V	
Light technic		
Type of light source:	LED	
Luminous flux:	1850lm	
Efficacy:	84 lm/W	
Colour temperature:	4000K	
Colour rendering (CRI):	Ra>90	
MacAdams factor:	SDCM: 2	
Lifetime:	L90/B10>100,000	
Light distribution:	Direct	
Optic:	Reflector	1
Beam angle:	35°	
Control/Dimming		Ø114
Туре:	Trailing edge dimming	
Protection		
Luminaire class:	Class II SELV	
Energy and approvals		105°
Contains light source of energy class:	E	
Breeam:	Fulfils Hea 01 for flicker free lighting	900
Materials and finish		
Housing:	Aluminium	75°
Colour:	White (RAL 9003)	
Optics:	Tempered glass	60* 800
Mounting/Connection		
Mounting:	Recessed, Indoor / Outdoor	1200
Connection:	Quick connector	450
Dimensions		1600
Height (mm) H:	130	
Diameter (mm) D:	114	2000
Cut-out (mm):	83	
Distance to flammable materials:	50mm	
Weight (kg) gross/net:	0.635 / 0.54	30°
Packaging		2800
Packing dimensions (mm):	152 x 143 x 140	
- · ·		1,5° 0°
		cd/klm





