

Namsen 1200 White 2110lm 3000K Ra>80 Trailing edge dimming

Article code: 112026
 EAN: 7021981120269



Electrical

System wattage: 27W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 35, B16: 57, C10: 58, C16: 95

Light technic

Type of light source: LED
 Luminous flux: 2110lm
 Efficacy: 78 lm/W
 Colour temperature: 3000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B50>50,000
 Light distribution: Direct
 Optic: Opal
 UGR: UGR<28
 Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfils Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Steel
 Colour: White
 Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Indoor
 Module: 1200
 Connection: Screwless terminal block

Dimensions

Length (mm) L: 1195
 Width (mm) W: 69
 Height (mm) H: 46
 Weight (kg) gross/net: 2.52 / 2.1

Packaging

Packing dimensions (mm): 1200 x 75 x 55

