

Prelude



Prelude White w/ 2 x outlet 1060lm 3000K Ra>90 Trailing edge dimming

Article code: 111349
EAN: 7021981113490




Electrical

System wattage: 14W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 23, B16: 37, C10: 29, C16: 46

Light technic

Type of light source: LED
Luminous flux: 1060lm
Efficacy: 76 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L70/B10>50,000
Light distribution: Direct
Optic: Opal
UGR: UGR<25
Photobiological safety: RG 0



Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I
IK Class: IK05
IP Class: IP44 (mounted horizontally) / IP20 (mounted vertically)

Energy and approvals

Contains light source of energy class: D
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Matte white (RAL 9003)
Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Surface, Indoor
Connection: Screwless terminal block

Dimensions

Width (mm) W: 630
Height (mm) H: 70
Depth (D): 80
Weight (kg) gross/net: 1.2 / 1.2

Packaging

Packing dimensions (mm): 630 x 80 x 90

