

## Sense White 320 1870lm 3000K Ra>80 Trailing edge dimming

Article code: 212281  
 EAN: 7021982122811



### Electrical

System wattage: 17W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

### Light technic

Type of light source: LED  
 Luminous flux: 1870lm  
 Efficacy: 110 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B20>100,000  
 Lifetime: L90>50,000  
 Light distribution: Direct  
 Optic: Opal  
 UGR: UGR<25  
 Photobiological safety: RG 0

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class II SELV  
 IK Class: IK08  
 IP Class: IP40

### Energy and approvals

Contains light source of energy class: D  
 Breeam: Fulfills Hea 01 for flicker free lighting  
 BVB: Yes

### Materials and finish

Housing: Aluminium  
 Colour: White smooth (Ral 9016 gloss 30)  
 Optics: Acrylic (PMMA)

### Mounting/Connection

Mounting: Recessed, Indoor  
 Connection: Screwless terminal block

### Dimensions

Height (mm) H: 25  
 Diameter (mm) D: 320  
 Cut-out (mm): 285  
 Ceiling void depth (mm): 25  
 Weight (kg) gross/net: 1.655 / 1.431

### Packaging

Packing dimensions (mm): 325 x 325 x 65

