

## Sense White 320 1950lm 4000K Ra>80 DALI / Push Dim

Article code: 212287  
 EAN: 7021982122873



### Electrical

System wattage: 17W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 35, B16: 55, C10: 57, C16: 92

### Light technic

Type of light source: LED  
 Luminous flux: 1950lm  
 Efficacy: 115 lm/W  
 Colour temperature: 4000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L80/B20>100,000  
 Lifetime: L90>50,000  
 Light distribution: Direct  
 Optic: Opal  
 UGR: UGR<25  
 Photobiological safety: RG 0

### Control/Dimming

Type: DALI / Push Dim

### Protection

Luminaire class: Class II SELV  
 IK Class: IK08  
 IP Class: IP40

### Energy and approvals

Contains light source of energy class: C  
 Breeam: Fulfils Hea 01 for flicker free lighting

### Materials and finish

Housing: Aluminium  
 Colour: White smooth (Ral 9016 gloss 30)  
 Optics: Acrylic (PMMA)

### Mounting/Connection

Mounting: Recessed, Indoor  
 Connection: 5 pol Linect / screwless terminal block

### Dimensions

Height (mm) H: 25  
 Diameter (mm) D: 320  
 Cut-out (mm): 285  
 Ceiling void depth (mm): 25  
 Weight (kg) gross/net: 1.489 / 1.265

### Packaging

Packing dimensions (mm): 325 x 325 x 65

