

Sense White 495 3800lm 4000K Ra>80 Trailing edge dimming

Article code: 212292
 EAN: 7021982122927



Electrical

System wattage: 33W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 32, B16: 51, C10: 32, C16: 51

Light technic

Type of light source: LED
 Luminous flux: 3800lm
 Efficacy: 115 lm/W
 Colour temperature: 4000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L80/B20>100,000
 Lifetime: L90>50,000
 Light distribution: Direct
 Optic: Opal
 UGR: UGR<22
 Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II SELV
 IK Class: IK08
 IP Class: IP40

Energy and approvals

Contains light source of energy class: D
 Breeam: Fulfills Hea 01 for flicker free lighting
 BVB: Yes

Materials and finish

Housing: Aluminium
 Colour: White smooth (Ral 9016 gloss 30)
 Optics: Acrylic (PMMA)

Mounting/Connection

Mounting: Recessed, Indoor
 Connection: Screwless terminal block

Dimensions

Height (mm) H: 29
 Diameter (mm) D: 495
 Cut-out (mm): 475
 Ceiling void depth (mm): 29
 Weight (kg) gross/net: 3.42 / 2.857

Packaging

Packing dimensions (mm): 505 x 505 x 65

