

Soft IsoSafe DimToWarm



Soft IsoSafe DimToWarm Black 470lm 2000-2800K Ra 98 Trailing edge dimming / Linect

Article code: 903223
EAN: 7021989032236



Electrical

Wattage: 7W
System wattage: 8W
Voltage: 220-240V
Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
Luminous flux: 470lm
Efficacy: 59 lm/W
Colour temperature: 2000-2800K
Colour rendering (CRI): Ra 98
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Light distribution: Direct
Optic: Glass Clear
Beam angle: 42°
UGR: UGR<19

Control/Dimming

Type: Trailing edge dimming / Linect

Protection

Luminaire class: Class II SELV
IP Class: IP54

Energy and approvals

Contains light source of energy class: F
Breeam: Fulfils Hea 01 for flicker free lighting
BVB: Yes

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: Tempered glass

Mounting/Connection

Mounting: Recessed, Indoor / Outdoor
Connection: 3 pol Linect / screwless terminal block

Dimensions

Height (mm) H: 53
Diameter (mm) D: 94
Cut-out (mm): 83
Ceiling void depth (mm): 51
Distance to flammable materials: 0mm
Weight (kg) gross/net: 0.696 / 0.58

Packaging

Packing dimensions (mm): 110 x 110 x 110

