Soft IsoSafe DimToWarm





Attractive downlight for indoor and outdoor use. Mounted directly in insulation. Well integrated LED chip with DimToWarm chip, dimmable via phase-dimming or DALI driver. It includes a junction box that provides strain relief for several types of cables, as well as fixtion for plastic tubing. Our IsoSafe products can be mounted directly in insulation (IsoSafe).

Soft IsoSafe DimToWarm



Product- and environment images







Article codes

Article		Protection	Control gear	Mounting/Connection	Dimensions
2000-2800K					
٢	903221 Soft IsoSafe DimToWarm White 550Im 2000-2800K Ra 98 Trailing edge dimming 8W LED 69 Im/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear	Class II SELV IP54	Trailing edge dimming	Recessed, Indoor / Outdoor Screwless terminal block	Ø94 x H53
	903223 Soft IsoSafe DimToWarm Black 470lm 2000-2800K Ra 98 Trailing edge dimming / Linect 8W LED 59 lm/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear	Class II SELV IP54	Trailing edge dimming / Linect	Recessed, Indoor / Outdoor 3 pol Linect / screwless terminal block	Ø94 x H53
۲	903231 Soft IsoSafe DimToWarm White 550Im 2000-2800K Ra 98 DALI-2 8W LED 69 Im/W SDCM:3 L90/B10>50,000 Beam: 42°, Direct, Glass Clear	Class II IP54	DALI-2	Recessed, Indoor / Outdoor 5 pol Linect / screwless terminal block	Ø94 x H53
Accessories					
0	9143 Rehab Ring Black 133mm for Junistar, Uniled, Soft & Jupiter Stainless steel				Ø133 x L133 x W133 x H4
0	9223 Rehab Ring White 133mm for Junistar, Uniled, Soft & Jupiter Stainless steel				Ø133 x L133 x W133 x H4
0	9224 Rehab Ring White 180mm for Junis	tar, Uniled, Soft & Ju	upiter Stainless steel		Ø180 x H45
0	9227 Rehab Ring White 250mm for Junis	tar, Uniled, Soft & Ju	upiter Stainless steel		Ø250 x H45
0	9236 Rehab Ring Black 180mm for Junis	tar, Uniled, Soft & Ju	piter Stainless steel		Ø180 x H45