

# Trio Socket



## Trio Socket Graphite w/ 2 x outlet 450lm 3000K Ra>80 Trailing edge dimming

Article code: 623525  
 EAN: 7021986235258



### Electrical

System wattage: 10W  
 Voltage: 220-240V  
 Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

### Light technic

Type of light source: LED  
 Luminous flux: 450lm  
 Efficacy: 45 lm/W  
 Colour temperature: 3000K  
 Colour rendering (CRI): Ra>80  
 MacAdams factor: SDCM: 3  
 Lifetime: L70/B10>50,000  
 Light distribution: Direct  
 Optic: Opal  
 Beam angle: 120°

### Control/Dimming

Type: Trailing edge dimming

### Protection

Luminaire class: Class I  
 IK Class: IK10  
 IP Class: IP44

### Energy and approvals

Contains light source of energy class: E  
 Breeam: Fulfils Hea 01 for flicker free lighting  
 BVB: Yes

### Materials and finish

Housing: Aluminium  
 Colour: Graphite  
 Optics: UV-stabilized polycarbonate

### Mounting/Connection

Mounting: Surface, Indoor / Outdoor  
 Connection: Screwless terminal block

### Dimensions

Length (mm) L: 320  
 Width (mm) W: 180  
 Height (mm) H: 320  
 Depth (D): 102  
 Weight (kg) gross/net: 1.9 / 1.625

### Packaging

Packing dimensions (mm): 330 x 190 x 110

