

Konverteringsguide

Gammal Lysrörsarmatur

Effekt	Ljusflöde	Systemeffekt
2x18W CFL	1440lm	41W
1x26W CFL	1080lm	31W
2x26W CFL	2160lm	56W
1x32W CFL	1440lm	36W
1x42W CFL	1920lm	47W
2x24W T5 HF	1750lm	52W
2x18W T8	1350lm	43W
4x14W T5 HF	2400lm	61W
4x18W T8	2700lm	86W
2x28W T5 HF	2600lm	60W
2x36W T8	3350lm	86W
2x49W T5 HF	4300lm	103W
2x58W T8	5200lm	139W
2x80W T5 HF	6150lm	166W



Sense Surface

Type	Ljusflöde	Systemeffekt	Energibesparing	Ljusflöde
370x370	1980lm	17W	59%	+38 %
370x370	1980lm	17W	45%	+83 %
370x370	1980lm	17W	70%	-8 %
370x370	1980lm	17W	53%	+38 %
370x370	1980lm	17W	64%	+3 %
640x200	1910lm	18W	65%	+9 %
640x200	1910lm	18W	58%	+41 %
600x600	3640lm	28W	54%	+52 %
600x600	3640lm	28W	67%	+35 %
300x1200	3790lm	29W	52%	+46 %
300x1200	3790lm	29W	66%	+13 %
300x1600	5330lm	41W	60%	+24 %
300x1600	5330lm	41W	71%	+2 %
300x1600	5330lm	41W	75%	-13 %